

Worksheet for risk assessment of VDU work

The worksheet is an oriented procedure for assessing working conditions. If the answer is "no", appropriate measures must be taken or further investigations are required. If you have any questions about risk assessment and ergonomics at the VDU workplace, the Occupational Safety and Environmental Protection group will be happy to advise you.

| Institute/Subject/Facility: | | | | | |
|--|-----|----|--|-----|----|
| Workplace/area of activity: | | | | | |
| Editor: | | | | | |
| Date: | | | | | |
| 1. Device Safety | yes | no | 4. Work table | yes | no |
| The equipment used in the workplace carry the CE and/or the GS mark. | | | Table width > 160 cm. | | Ш |
| | | | Table depth > 80 cm. | | |
| 2. Screen | | | Total area for table combination > 1,28 m ² | | |
| The top line of the screen is at most at eye level. | | | Table height: adjustable (68-85) cm or 72-76cm for table not adjustable in height. | | |
| | | | Legroom height: > 65 cm. | | |
| | | | Legroom width: > 85 cm. | | |
| | | | Legroom depth: > 80 cm. | | |
| | | | 5. Swivel chair5-caster base with braked rollers, depending on the hardness of the floor covering | | |
| | | | height adjustable | | |
| The screen can be easily rotated and tilted. | | | padded seat, rounded front edge | | |
| The screen diagonal is > 15 inches (visible 35 cm) or for graphics and other applications > 17 inch (visible 40 cm). | | | padded and adjustable backrest with Support in the lumbar region. | | |
| The screen is free from disturbing Reflections. | | | Dynamic sitting (change of posture) is possible. | | |
| 3. Keyboard/Mouse The keyboard is separate from the screen (not a laptop). | | | | | |
| The keyboard is slightly inclined, the center letter row has a height of < 3 cm. | | | | | |
| In front of the keyboard, a free table area of (5-10) cm for placing the heel of the hand is available. | | | | | |
| Mouse and mouse pad are located in the small gripping space (< 30 cm from table front edge). | | | | | |

Revision: 03 | 24.04.2024 1/2

| 6. Adaptation of the work equipment to the body dimensions | yes | no | 9. Other working environment Noise: sufficiently quiet (office < 55 dB [A]) | yes | no |
|---|-----|-----------------------------|--|--------|-----------|
| Forearm approximately horizontal, hands at keyboard height, angle between upper and lower arm > 90° | | | , | | |
| | | | Climate: room temperature 20° C to 26° C Humidity pleasant (40-65%) | | 2.) |
| Upper thigh approximately horizontal, angle between upper and lower thigh > 90. | | | Draft-free (air velocity < 0.15 m/s) | | 2.) |
| Full support of the feet on the floor is possible (if not, footrest is required). | | | 10. Man machine interface ^{3.)} The information is presented in positive (dark characters on light background). | | |
| The footrest is present if necessary. | | 1.) | The system provides information/help about the | | |
| Full-surface foot support on the footrest is possible, area > $(45 \times 35) \text{ cm}^2$. | 1.) | | respective process. | | |
| | | | The information is displayed in a format and pace adapted to the user. | | |
| 7. Space requirement/Workplace arrangemen | t | 11. Organizational measures | | | |
| Area per workplace > 8 m ² , in open-plan offices >12 m ² . | | | It is possible to interrupt screen work by changing activities or taking short breaks. | | |
| Free movement area at the workplace $> 1.5 \text{ m}^2$ | | | The employees were instructed in the use of the visual display unit. | | |
| Minimum depth 1,0 m | | | | | |
| Connecting corridors to personal workplace > 0.6 m | | | The employees or their representation (works council / Staff Council) were involved in setting up the display workstation. | | |
| trip-free (note e.g. cable routing) | | | | | |
| View parallel to the window front | | | | | |
| View parallel to luminaire strips | | | 12. Precautionary measures | | |
| | | | Employees are informed about possible health impairments and are aware of measures for avoidance. An initial or follow-up examination of the | | |
| | | | employees' eyesight was offered. | | |
| | | | 13. Other measures | | |
| 8. Lighing | | | A review of the workplace for other reasons can be waived. | | Ш |
| Bright enough (>500 lx) | | 2.) | A further assessment of the workplace is required | | |
| The lamps / lights do not dazzle. | | | in the case of particular mental stress (e.g. in the case of predominant data collection). | | |
| The surfaces of the devices and tables are matt. | | | (| | |
| The lighting does not flicker. | | | | | |
| Only lamps of the same light color are present. | | | | | |
| Exterior blinds or interior roller blinds regulate the sunlight incidence. | | | | | |
| sumgit incluence. | | | evaluate only if necessary. subjective assessment sufficient. When procuring the software, it must be checked weth DIN EN ISO 9241-110 is fulfilled. | er | |
| Source: The checklist was compiled on the basis of a publication by the Federal State Committee for Occupational Safety and Safety Technology (2007). | | | Image credits: - BG ETEM "Bildschirmarbeitsplätze" - DGUV-Information 215-410 "Bildschirm- und Büroarbeitsp | lätze" | |

Revision: 03 | 24.04.2024 2/2